

'THE HS 5030TT EVO2 Is The Most Versatile, Flexible, Mobile Baggage X-Ray Machine On The Market'

The **HS 5030TT EVO2** is the most versatile, mobile baggage x-ray machines on the market. Designed for rapid deployment, minimal space availability and flexibility in location makes the **HS 5030TT EVO2** one of the most sort after units on the market. An ideal solution for police, military, events, shows and high security locations, this unit can be easily transported and deployed as and when required.

The standard configuration is an operator console, placed on top of the machine with a monitor making it versatile in any application. Options for a 'fold down' touch screen interface are available on request as well as custom built mobile trolleys with large wheels and vehicle specific ramps for easy transportation.

SPECIAL FEATURES

- 5 year Parts Inclusive Warrant Only
- CIRTIS (Computer Item Recognition Training Software)
- Ultra-Compact design
- Self-diagnostics capability
- Organic / inorganic stripping
- Image archiving

ADDITIONAL EXTRAS

- Mobile Trolley
- Roller tables (entry/exit) built to any length
- Fold Down Touch Screen Interface



'THE HS 5030TT EVO2 Is The Most Versatile, Flexible, Mobile Baggage X-Ray Machine On The Market'

SPECIFICATIONS

GENERAL

| | |
|------------------------------|-----------------------------|
| Construction: | Steel based |
| Tunnel Size: | 505 mm (W) x 305 mm (H) |
| Length / Width / Height (mm) | 1210 (L) 750 (W) x 745 (H) |
| | 290 Kgs (uncrated) |
| | 450 Kgs (crated) |
| Conveyor Height: | 145 mm from the floor |
| Conveyor Speed: | 0.20 meters per second |
| Maximum Conveyor Load: | 100 Kg (evenly distributed) |
| System Noise Level: | <55 dB |

PERFORMANCE INDEX *

| | |
|--------------------------|---|
| Penetration: | 22 mm Steel (guaranteed) 24 mm Steel (typical) |
| Resolution (wire gauge): | 32 AWG (guaranteed) 34 AWG (typical) |

X-RAY GENERATOR

| | |
|-----------------------|-----------------------------------|
| Tube Voltage: | 100 kV (Fixed) sealed oil bath |
| Tube Current: | 0.3 - 1.0mA (adjustable) |
| Cooling / Duty Cycle: | Sealed oil cooling / 100% |
| Beam Launch Angle: | 80 degrees |

OPERATIONAL INDEX

| | |
|------------------------|---|
| Storage Temp/Humidity: | -20°C to 50°C 10% - 95% non-condensing |
| Working Temp/Humidity: | 0°C to 45°C 10% - 95% non-condensing |
| Working Voltage: | AC 220V ± to 10%) 50 Hz / 60 Hz ± 3 Hz |
| Power: | 0.5 kVA |
| Leakage: | <0.5µ Sv / H |
| Dose Per Inspection: | <1.5 µ Sv (typical) |
| Duty Cycle: | 100% (no burn in necessary) |

IMAGING

- Image resolution: 1280 x 1024 x 24 bits
- Zoom 2 - 64 x (dynamic, smooth and continuous)
- Full screen zoom (one click)
- High, low penetration
- Organic / inorganic stripping
- Picture pure (no distortion)
- Super edge enhancement capability
- Automatic 100x screen image recall (last in first out)
- Dual-energy technology
- Colour, black and white display

IMAGE RECALL

- 500,000 Images storage capacity (standard)
- Image conversion and export to jpg, png and bmp
- Image search and simulated playback

ADDITIONAL FEATURES

- 21" High resolution Touch Screen Interface
- Input / Exit Rollers to any length required
- Mobile Trolley
- Mobile Ramps (Vehicle Specific)
- 5 Years Parts Inclusive Warranty Only

COMPLIANCE STANDARDS

- Complies with film safety ISO 1600 / 33 DIN high speed photographic film
- All equipment is CE (Europe) certified and manufactured to ISO 9001 standards, FDA 21CFR- Part 1003/1004 approved for use in the USA.
- Radiation safety: Meets all applicable laws and regulations with respect to X-ray emitting devices, with directives, 2014/30/EC, 2014/35/EC, 2006/42/EC, FDA 21CFR, SAPHRA.
- *Propriety quality management test piece: Steel Step Wedge, CU wires, Shims, Organic Inorganic, Belt speed 0.20 m/s.
- *Approximate Values (Adjustable)

